


STI SELECT-ALERT



STI-SA5000-R and
KIT-71100A-W



PRODUCT OVERVIEW

Here is a highly effective way to alert you to any unauthorized use, theft or vandalism of important devices, as well as unauthorized exits and entries. The combination of alert and super bright flashing LEDs offers excellent protection for an array of circumstances as they draw attention in a hurry. Select-Alert allows you to choose its function and can be used as a cabinet alert, door/exit alert, flashing light linked with a push button/switch, tornado siren, or an alert for many types of emergency situations.

HOW IT WORKS

When installed as a cabinet or door alert, with the optional reed switch and magnet, Select-Alert emits an ear piercing siren and the LEDs flash when the protected unit is opened. The alert and strobe have independent timing choices of: 15 seconds, 30 seconds, 60 seconds or continuous and the alert has an option of 32 tones. Can be powered by a 9 VDC battery or external 12 - 24 volts. Flush or surface mount Select-Alert is available in amber, green, blue, red or white.

KEY FEATURES

General Information

- Alerts to any unauthorized use, theft or vandalism of important devices, as well as unauthorized exits and entries.
- Alert offers 32 tones.
- Includes ten high intensity LEDs.
- For indoor use only.
- Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

Construction

- Durable, polycarbonate construction.

Installation

- Includes a tamper switch which prevents it from being removed from a wall.
- Typical working properties of polycarbonate are -40° to 250°F (-40° to 121°C).

Electronics

- May be set for a piercing 100 dB alert or a softer 85 dB.
- One Form "C" dry relay contact output.
- Powered by a 9 VDC battery (not included) or external 12 – 24 volts.
- Low battery indicator.

Options

- Can be used as a cabinet alert, door alert, link with push button/switch.
- Available with amber, green, blue, red or white lens.

STI Select-Alert

Dimensions and Technical Information

MODELS AVAILABLE

STI-SA5000-A	Amber
STI-SA5000-B	Blue
STI-SA5000-G	Green
STI-SA5000-R	Red
STI-SA5000-W	White

Accessories

KIT-71100A-*	Back box kit
KIT-H18075	Replacement key for Select-Alert
KIT-H19016	Two Tamper Wrenches
KIT-E18151	Open circuit reed switch and magnet
KIT-SA505	Key switch mounting bracket (includes key switch and two keys)
KIT-M05050-*	Replacement Lens


* Add 'A' for amber/orange, 'B' for blue, 'G' for green, 'R' for red, 'W' for white

WARRANTY


Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

SPECIFICATIONS

Operating voltage	Internal 9 VDC battery (not included) Remote power 12-24 VDC
Power consumption	Stand by: 50µA Siren low volume: 85mA Siren high volume: 90mA Strobe: 25mA
Siren Volume	Low: 85 dB at 1' High: 100 dB at 1'
Alert and Strobe Timing	Independent control for siren and strobe: 15s, 30s, 60s, continuous
Low Battery Warning	LEDs flash once every 30 seconds
Form C dry contacts	0-30VAC/DC, 1 Amp Contacts reset after longest alert setting
Key Switch	Alert on: normally closed
Alert Circuit	Open circuit (close goes to alert)
Alert Tone	32 selectable sounds



FRONT



SIDE



**Safety Technology
International**

2306 Airport Road info@sti-usa.com
Waterford, MI www.sti-usa.com
48327, USA Tel:248-673-9898

Taylor House
34 Sherwood Rd., Bromsgrove,
Worcs., B60 3DR, England

info@sti-emea.com
www.sti-emea.com
Tel: +44 (0) 1527 520 999

Unit 7A Lockheed Avenue
Airport Business Park
Waterford X91 HWF2 Ireland